


Data sheet

Part No.	SGL BK UV
Description	straight gland for corrugated conduits, with patented plug-in system for quick-fit assembly, pull-tight connection, with metric thread according to EN 60423
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	IP54



Standard: EN 61386-1, EN 61386-23, EN 60754
halogenfree according to EN 60754



Working temperature	Degree of protection (IP)	UV resistant
-25 to +105 °C	IP54	true – up to 10 years

Art. No.	Nominal diameter	Thread	Thread length	Total length	PU	PU
027797	12 mm	M12 x 1.5	8 mm	18,3 mm	100 pc	3200 pc
027798	16 mm	M16 x 1.5	10,5 mm	18,9 mm	100 pc	1600 pc
027799	20 mm	M20 x 1.5	12 mm	24 mm	50 pc	1200 pc
027800	25 mm	M25 x 1.5	15 mm	30,4 mm	50 pc	600 pc
027801	32 mm	M32 x 1.5	15 mm	32 mm	30 pc	360 pc
027802	40 mm	M40 x 1.5	15 mm	38 mm	20 pc	240 pc
027803	50 mm	M50 x 1.5	15 mm	42,4 mm	16 pc	128 pc
027804	63 mm	M63 x 1.5	20 mm	54 mm	8 pc	64 pc

Further technical details

Details	
Model	Straight
Revolving thread	False
Construction type	External thread
Material	PA-Blend