



List No. NHTN04L

NH DISTRIBUTION

4-Way 125A Surface 3P+N Distribution Board



- 4W 3P+N Type 'B' distribution board
- Switch disconnecter, RCCB, or direct connection incomer options available
- Accepts Wylex 10kA and miniature 6kA final circuit protection devices; Single and Triple Pole MCBs from 6A to 63A, Single Pole RCBOs from 6A to 50A and AFDDs from 6A to 40A
- Accepts the Wylex NHCM125INMP (Pulsed Output/Modbus RTU), NHMID125INMP (MID) integral incoming meter kits or NHTNSP125L integral Type 2 surge protection kit
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data

Revision Date: 07/12/2022

| | |
|----------------------------------|---------------------------|
| Mounting method | Surface mounted (plaster) |
| Number of phases | 3 |
| Main switch rated current | 125 A |
| Material housing | Steel |
| Degree of protection (IP) | IP31 |
| Height | 490 mm |
| Width | 430 mm |
| Depth | 155 mm |
| Extension possible | Yes |
| With transparent cover | No |
| Lockable | Yes |
| Product Standard/s | BS EN 61439-3 |
| Frequency | 50 Hz |
| CE Conformity | Yes |
| WEEE Symbol | Yes |
| UKCA Conformity | Yes |
| Number of ways (Type 'B' boards) | 4 |
| Amperage | 125 A |
| Pole Configuration | TPN |
| Operating Voltage | 400 V |
| Type of Current | AC |
| Busbar type | FIXED SOLID COPPER |
| Colour RAL | 7035 |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.