

FESTOON

110V EXTENDABLE FESTOONS

Our Connectable Festoon Kit range is now bigger and better, with the addition of 22m and 50m kits in addition to the original 12m kit. All feature our unique connector and can be joined together in any combination up to a maximum length of 150m. This makes extending the festoon on site simple and easy, saving time and money.



Features

- Designed in the UK by Red Arrow
- Extendable up to 150m long
- Robust, high efficiency LED heads
- Pre-wired with industrial 3 pin plug
- IK07 rated for site applications



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
FKF2250W	Festoon Kit Connectable 10-Way 22m	5500lm		50W	110 lm/W

Product Information

Warranty	2 Years
Colour Appearance (CCT)	6000K
IP Rating	IP44
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	0.9
Frequency	50Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C





FESTOON

110V EXTENDABLE FESTOONS

Packaging Information

Dimensions (mm)	L: 22m Head: H: 60 x Ø: 75 mm
Product Net Weight (kg)	2.2 kg
Barcode	5055807624350
Box Dimensions (mm)	L: 260 x W: 260 x D: 155 mm
Box Gross Weight (kg)	4.7 kg

Units/Outer Carton	4
Outer Carton Barcode	15055807624357
Outer Carton Dimensions (mm)	L: 540 x W: 275 x D: 335 mm
Outer Carton Gross Weight (kg)	10.3 kg



ENERGY
Red Arrow
 FKF

A
 B
 C
 D
E
 F
 G

30-100
 kWh/1000h