

ActiV Relay Base with Diode

Part No. **C4408DR**



Overview

- Compatible with C-TEC's entire range of ActiV fire detectors.
- Includes a 1A @ 24 VDC relay controlled by detector's remote LED output.
- Ideal for switching CCTV, security and door retaining systems.
- Third-party certified to the relevant parts of EN54 in conjunction with our ActiV detectors.
- Easy to fit with lots of working space.
- Can be ceiling mounted in any orientation due to the true 360° degree viewing angle of the LED indicator strips on all ActiV detectors.
- Integrated detector/base locking mechanism, head removal tool and ID tag.
- Simple 'click and twist' design.
- Remote LED terminals for the optional connection to a BF318 Remote indicator.
- C4408R non-diode relay base also available for use on systems that do not require head out monitoring.



More Information

Technical Specifications

Approvals/certifications Certified to the relevant parts of EN54 by Intertek as part of our ActiV fire detector certifications.

Supply wiring 2-wire monitored, polarity sensitive.

Connections (1) +V In; (2) +V Out; (3) Remote LED +V; (4) 0V; (5) 0V; (6) Screen; (7) Screen. NO/C/NC relay connections. Contact rating @ 24VDC is 1A. Terminals can accept up to 2.5mm fire rated cable.

Product dimensions (mm) 102.2mm diameter x 30mm deep.



T 01942 322744

F 01942 829867

E sales@c-tec.co.uk

W www.c-tec.com





Construction & finish	White polycarbonate rated to UL94 V-2 with bright tin plated steel terminals fitted with nickel plated steel screws/washers.
IP Rating	IP42.
Weight	86g



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom