



RF SMOKE ALARM

BATTERY-OPERATED | MODEL 2106

CAVIUS 78MM SMOKE ALARM WITH RF CONNECTIVITY



Overview & Key Features

Battery-operated 78mm diameter optical smoke alarm in the Cavius family, with built-in RF connectivity. Can be interlinked with up to 31 other Cavius devices including RF smoke and heat alarms, Cavius relay and ancilliary devices.

- Grade F1
- 10-year sealed-in battery life – never needs replacing
- Designed for domestic use including motorhomes and caravans
- Dual insect screen to minimise nuisance alarms
- Wall and ceiling mounting options
- Quick and easy set-up and coding
- Certified to EN 14604:2005 + AC:2008
- 10-year manufacturer's warranty

Technical Specifications

General

Order code:	CV2106
Compatibility:	Cavius RF alarm family
Primary Power Source:	10-year sealed-in lithium battery
Product & Battery Life:	10-years
Low Battery Warning:	Yes
Sound Output:	85 dB (A) at 3 metres
Alarm Frequency:	869.675 MHz, max 20 mW
Wireless Range:	>100 m open field
Mounting Options:	Wall or ceiling
Number of interconnected units:	32
Operating Temperature Range:	+4°C to +38°C
Storage Temperature Range:	-20°C to +60°C
Humidity Range:	Up to 90% RH (non-condensing)

Weights and Dimensions

Alarm Dimensions:	78mm x 40mm
Alarm Weight (including batteries):	105g
Case Quantity:	10 units

Warranty

10-year manufacturer's warranty