


10A Modules



Description

A range of switch modules which are easy to install, have clear terminal markings and are supplied in individually in protective bags.

Red rocker versions are available to distinguish between essential supplies.

Features

- Curved rockers
- Red rocker versions available
- Front loading into grid frame
- Switches are X rated and do not have to be de-rated for fluorescent loads
- Clear terminal markings
- Grey font engraving
- Only one size 4mm screwdriver needed
- 25-year guarantee

Range

White inserts

| | |
|----------------------------|---------|
| 1-way switch | G3501* |
| 2-way switch | G3502 |
| 2-way 'press' switch | G3503 |
| 2-way 'press' – red rocker | G3503RD |
| 2-way push to make switch | G3506 |

Black inserts

| | |
|----------------------------|----------|
| 2-way | G3502BK |
| 2-way 'press' | G3503BK |
| 2-way 'press' – red rocker | G3503RDB |
| 2-way push to make switch | G3506BK |

Suffix finish with

| | |
|------------------------|--------|
| Chrome | CH |
| Stainless Steel | SS |
| White or Black inserts | W or B |

**Available in white finish only*

Technical Specification

| | |
|----------------|------------|
| Voltage rating | 250Vac |
| Current Rating | 10AX rated |
| Contact gap | 3mm |

No user serviceable parts

Back Boxes

Minimum recommended depth

| | Flush 25mm | Dry lining 35mm | Surface 25mm |
|----|---------------|--------------------|-----------------|
| 1g | DB162 | DB2540 | V1221 |
| 2g | DB163 | DB2541 | V1223 |

Standards

- BS EN 60669-1 : 2018

Terminal Capacity

| | 1mm ² | 1.5mm ² | 2.5mm ² | 4mm ² |
|-------|------------------|--------------------|--------------------|------------------|
| L & N | 6 | 6 | 4 | 2 |