

# JC1101/WH10

## X50

X50 Fire rated downlight 3W/5W IP65 3000/4000/5700K 480/700 lms White (10 pack)

### Features & Benefits

- Two wattage and three colour selectable from beneath the ceiling
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings
- Multipack of 10 with white bezel (JC1101/WH10)
- Triac dimmable as standard, see JCC.co.uk for approved dimmer list



### General Information

Mounting	<b>Recessed</b>
Environment	<b>Demanding</b>
Suitable For Zones	<b>Zone 1</b>
Product Group	<b>Fire-rated Downlights</b>
Color Finish	<b>White</b>
Product Shape	<b>Round</b>
Product Range	<b>X50</b>
Overall Dimensions	<b>84Ø x 55.4 x 322 cm (see profile drawing for details)</b>
Length (mm)	<b>322</b>
Height (mm)	<b>55.4</b>
Diameter (mm)	<b>84</b>
Product Weight(kg)	<b>0.266</b>
Light Source	<b>LED</b>
Light Source Features	<b>3CCT Switchable</b>
Additional Information	<b>For Emergency version, use JC131003 only. Not suitable for use with JCEM002/JCEM002ST</b>
Recommended product location	<b>Indoor use only</b>

Minimum Void Requirement	<b>50mm</b>
Method of fix	<b>Spring clips</b>
Distance from lighted object	<b>0.3m</b>
IP Rating	<b>IP65</b>
Duration of Fire protection ( Mins)	<b>Tested for use in fire-rated ceilings. Full information and upto-date fire testing certificates for ceiling system types are available on JCC.CO.UK</b>
Origin of manufacturer	<b>China</b>
Warranty	<b>5 Year Warranty(Terms &amp; conditions apply)</b>
Dimming Protocol Compatibility	<b>Triac dimmable</b>
Driver manufacturer	<b>JCC</b>
Lighting Product Type 1	<b>Downlight</b>
Lighting Product Type 2	<b>Fire-rated</b>

## Electrical

Voltage Rating	<b>230-240</b>
Primary Running Current(Amp)	<b>0.0018/0.0026</b>
Operating Frequency Hz	<b>50/60</b>
Secondary running current(mA)	<b>0.0083/0.0127</b>
Constant Current or Constant Voltage	<b>CC</b>
Luminaire Circuit Wattage1	<b>3</b>
Luminaire Circuit Wattage2	<b>5</b>
Class	<b>I</b>
EMC Compliant (EN55015)	<b>Yes</b>
Input Electrical Connections	<b>Live, Earth, Neutral</b>
Dimmable	<b>Yes, Triac dimmable only</b>

## Thermals

Thermal Cut Out	<b>Yes</b>
Insulation Coverage	<b>Loosely Cover with Mineral Wool Insulation</b>
Minimum Void Requirement	<b>50mm</b>
Operating Temperature Range °C	<b>0 to 26</b>

## Performance Data

LED Life (Hours)*	<b>88000</b>
Energy Rating	<b>This product contains a light source of energy efficiency class B(3W) or C (5W) for selected Wattage</b>
Actual Lumen Output1	<b>480</b>
Actual Lumen Output2	<b>700</b>
Lumens Per Circuit Watt1	<b>160</b>
Lumens Per Circuit Watt2	<b>140</b>
Color Rendering Index	<b>80-89</b>
CRI: Ra	<b>80</b>
Correlated Colour Temperature1	<b>3000</b>
Correlated Colour Temperature2	<b>4000</b>




Correlated Colour Temperature	3	5700K
Beam Angle	°	60°
LOR (Light Output Ratio) %		100
Photometry Available		Yes

## Packaging

Product Bar Code EAN-13 Number	5052544121623
--------------------------------	---------------

## Standards & Approvals

Manufactured in accordance to	BS EN 60598:2015, 2-1, 2-2
CE Marked	Yes
UKCA Marked	Yes
Date code/Purchase order No.	Yes
WEEE symbol	Yes
Certificate Of Conformity	available on request
Accredited Members	LIA, ISO9001-2015, ISO14001-2015



\*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.  
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | [sales@jcc.co.uk](mailto:sales@jcc.co.uk) | [www.jcc.co.uk](http://www.jcc.co.uk)  
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 86 [02/04/2025]