Knightsbridge

DATASHEET

OSPCR

230V 5A IP65 Photocell Switch

www.mlaccessories.co.uk

MLA PART CODE	**OSPCR**
DESCRIPTION	230V 5A IP65 Photocell Switch
NET WEIGHT (KG)	0.045
FINISH	Black
DIMENSIONS (MM)	Length - 52.5 Width - 29 Projection - 21 Overall Height - 42
CUT-OUT (MM)	Cut-out Diameter - 17
MINIMUM MOUNTING BOX DEPTH	25mm
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD	500W Incandescent / 850VA Inductive / 300W LED
FUNCTION	Time delay: 20~120 seconds
CABLE LENGTH (M)	0.3
SENSOR TYPE	Photocell
SENSOR OVERRIDE	No
SENSOR LUX SETTINGS	On – 10~20lux / Off – 30~60lux
STANDBY POWER	1.2W
WARRANTY	2year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270877069

Date Created: 21/11/2025 09:01

ML ACCESSORIES LTD

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.