



Features

PVC Sleeving

- High-grade PVC construction.
- Self-extinguishing in 30 seconds.
- Available for a range of cable diameters.

Heat Shrink

- 2:1 shrink ratio.
- Multipack contains 3 x 250mm of each colours: Brown, Black, Grey, Blue, Green/Yellow.

Compliance

- BS EN 60684

Sleeving and Heat Shrink

Description

A wide range of sleeving and heat shrink is available in the Installation Materials range.

Sleeving is used for identification, while heat shrink can be used for identification and repairing damaged cable insulation.

Range

PVC Sleeving

Green/Yellow

2mm x 100m Earth Sleeving	27GY2
3mm x 100m Earth Sleeving	27GY3
4mm x 100m Earth Sleeving	27GY4
5mm x 100m Earth Sleeving	27GY5
6mm x 100m Earth Sleeving	27GY6

Green/Yellow - Reels

3mm x 100m Earth Sleeving	27GY3R
4mm x 100m Earth Sleeving	27GY4R

Blue

3mm x 100m Sleeving	27BU3
4mm x 100m Sleeving	27BU4

Brown

3mm x 100m Sleeving	27BR3
4mm x 100m Sleeving	27BR4

Multi Reel

3mm x 100m Earth Sleeving Multi-Reel (Green/Yellow 60m, Blue - 20m, Brown - 20m)	27MR3R
--	--------

Heat Shrink Multipacks 250mm Lengths

(Packs of 15)

6.4mm Diameter - Black, Blue, Brown, Grey, Green/Yellow x 3	29HSM02
9.5mm Diameter - Black, Blue, Brown, Grey, Green/Yellow x 3	29HSM03
12.7mm Diameter - Black, Blue, Brown, Grey, Green/Yellow x 3	29HSM04
19.1mm Diameter - Black, Blue, Brown, Grey, Green/Yellow x 3	29HSM05
25.4mm Diameter) - Black, Blue, Brown, Grey, Green/Yellow x 3	29HSM06