

MODT15D

7 Day Digital Timer Datasheet



CONSTRUCTION AND FEATURES:

- Module Width
- Electronic with LCD display
- Switch Loads up to 16A
- 7 day 24 hour ON/OFF programming
- Permanent ON/OFF switching
- Battery back up
- DIN Rail or panel mount
- Fits into standard enclosures & consumer units

TECHNICAL DATA:

- Rated voltage: 230V AC
- Rated frequency: 50/60Hz
- Switch loads up to 16A with power factor 1.0 (25A if power factor 0.6)
- Contact: 1NO+1NC
- Consumption: maximum 4VA
- Contact capacity:
 - - 16A/250V AC (COS Φ = 1)
 - - 25A/250V AC (COS Φ = 0.6)
- Incandescent lamp: 1000W
- Electrical endurance: 105 cycles
- Mechanical endurance: 107cycles
- Time basis: quartz
- 24 hours+ week program
- Working Precision: < 2 sec/day (250 C)
- Min. programmable interval: 1 minute
- Power reserve: min. 15 days
- Ambient temperature: -10-400C
- Humidity: 35-85% RH
- Connection terminal: pillar terminal with clamp
- Connection capacity: rigid conductor 6mm²
- Installation: On symmetrical DIN rail or panel mounting

DIMENSIONAL SKETCH:

