

ESPIRE



Product Code: ES1SRV

Description: Optical Smoke Alarm Powered by Mains with a Replaceable 9V Battery

Technical Specification Sensor Alarm

Luckinslive 437540298

ESP
ScolmoreGROUP



General Information

Dimensions (mm)	Ø132 x 52
Colour	White
Materials	UL94-V0 rated UV stabilised ABS
Mounting	Ceiling or Wall
Recommended Installation Locations	Living Areas, Bedrooms, Escape Routes & Stairways
Indication	3 LEDs; Green - Power, Yellow - Fault, Red - Fire
Auto Dim Power LED	Day Mode and Night Mode (Not intrusive to sleep)
Manual Test Button	Checks sensor, electronics & sounder
Weight (Kg)	0.25
Warranty (Years)	5

Technical

Sensor Type	Optical Smoke
Sounder Output (dB)	85 @ 3m
Hush Function	Alarm hush - 10 minutes, Fault hush - 12 hours
Installation Grade	D2

Supply, Power & Backup

Supply Type	Mains AC with battery backup
Supply Voltage (V AC)	230
Frequency (Hz)	50
Maximum Power Consumption (W)	1
Standby Power Consumption (W)	0.2
Battery Backup	Replaceable Battery
Battery Type	9V Alkaline
Battery Size	PP3
Battery Chemistry	Alkaline

Interconnectability

Wired Interconnect Supported	Yes
Maximum Interconnect Wiring Distance (m)	300
RF-LINK Supported	No
Maximum Supported Wired & RF-LINK Interconnected Devices	28

Environment

Operating Temperature (°C)	0 to +40
Relative Humidity Resistance (%)	95 (non-condensing)

Accessories

ES1MP: Alarm Masking Plate
ES1MTW: Alarm Multi Tool (2 Pack) White
ES1MTB: Alarm Multi Tool (2 Pack) Black

Features

Dust compensation
Insect mesh
Lock-in wiring base
24 hour memory function
Clear LED indication status



Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuke.com | W: espuke.com

CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN