

Circuit Protection / MK Sentry

MCB SINGLE POLE TYPE C 6A 230V C6



Technical Specification

Product Code	H8706S
Breaking Capacity (kA)	6000
Country of Origin	CHINA
Degree of Pollution	2
Energy Limiting Class	3
IP Rating	IP20
Maximum Installation Altitude (m)	2000
Maximum Operating Temperature (°C)	55
MCB Curve	C
Minimum Operating Temperature (°C)	-5
Number of Modules	1
Number of Poles	1
Operation Frequency (Hz)	50-60
Pack Quantity	12

Tel No: 01279 772 772

Email: sales@greenbrook.co.uk

Website: www.greenbrook.co.uk

Package Product Max. Length (mm)	230
Package Product Max. Depth (mm)	78.5
Package Product Max. Width (mm)	92
Package Weight (kg)	0.0083
Packaging Material	CARDBOARD - RECYCLED
Product (only) Max. Depth (mm)	71
Product (only) Max. Height (mm)	83
Product (only) Max. Width (mm)	18
Product Weight (kg)	0.11
Rated Impulse Withstand Voltage (v)	40000
Rated Operational Current (A)	6
Rated Operational Voltage (v)	230
Rated Tripping Current (mA)	n/a
RCD Type	n/a
Standards	BSEN60898-1
Terminal Capacity (mm²)	25
Tightening Torque (Nm)	3

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk