

## Circuit Protection / MK Sentry

### MCB SINGLE POLE TYPE C 10A 230V C10



## Technical Specification

<b>Product Code</b>	H8710S
<b>Breaking Capacity (kA)</b>	6000
<b>Country of Origin</b>	CHINA
<b>Degree of Pollution</b>	2
<b>Energy Limiting Class</b>	3
<b>IP Rating</b>	IP20
<b>Maximum Installation Altitude (m)</b>	2000
<b>Maximum Operating Temperature (°C)</b>	55
<b>MCB Curve</b>	C
<b>Minimum Operating Temperature (°C)</b>	-5
<b>Number of Modules</b>	1
<b>Number of Poles</b>	1
<b>Operation Frequency (Hz)</b>	50-60
<b>Pack Quantity</b>	12

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)

Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)

<b>Package Product Max. Length (mm)</b>	230
<b>Package Product Max. Depth (mm)</b>	78.5
<b>Package Product Max. Width (mm)</b>	92
<b>Package Weight (kg)</b>	0.0083
<b>Packaging Material</b>	CARDBOARD - RECYCLED
<b>Product (only) Max. Depth (mm)</b>	71
<b>Product (only) Max. Height (mm)</b>	83
<b>Product (only) Max. Width (mm)</b>	18
<b>Product Weight (kg)</b>	0.11
<b>Rated Impulse Withstand Voltage (v)</b>	40000
<b>Rated Operational Current (A)</b>	10
<b>Rated Operational Voltage (v)</b>	230
<b>Rated Tripping Current (mA)</b>	n/a
<b>RCD Type</b>	n/a
<b>Standards</b>	BSEN60898-1
<b>Terminal Capacity (mm<sup>2</sup>)</b>	25
<b>Tightening Torque (Nm)</b>	3

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)