

MAGDUO

Technical Specification



Product Code: MAGDUOSSLP

Luckinslive 406864206

Description: Low Profile Dome Sounder and Strobe



General Information

Dimensions (mm)	ø105 x 45
Volume Modes	2 (Low & High)
Device Loading Units (DLU's) - Low	33
Warranty (Years)	3

Supply & Power

Operating Voltage (Mains Powered Panel)(V DC)	25.5 - 35
Operating Voltage (Battery Powered Panel)(V DC)	24 - 26
Maximum Cable Size (mm ²)	1.5
Current Consumption (Quiescent)(mA)	0.22
Current Consumption in alarm state (mA)	High 23.5, Low 15
Maximum Current Consumption	23.5mA
Wiring Type	2-Wire Conventional

Inputs & Outputs

Sound Output @ 1m (Low) (db)	65+
Sound Output @ 1m (High) (db)	90+

Environment

Ingress Protection	IP21C
Operating Temperature (°C)	-10 to +50

Compatible Products Compatible with MAGDUO2, MAGDUO4 and MAGDUO8

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuke.com | **W:** espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN